





SPECIFICATION

ITEM	DC12V SP- 600	DC24V SP- 600
OUTPUT POWER	600W CONTINUOUS POWER 1500W SURGE POWER	600W CONTINUOUS POWER 1500W SURGE POWER
STANDBY CURRENT	DC 12V < 0.5A	DC 24V < 0.3A
INPUT VOLTAGE	DC 10V~15V	DC 20V~30V
OUTPUT VOLTAGE	AC 100V, 110V, 120V, 220V, 230V, 240V	AC 100V, 110V, 120V, 220V, 230V, 240V
OUTPUT WAVEFORM	Modified Sine Wave 	Modified Sine Wave 
EFFICIENCY	> 85%	> 85%
※ INITIAL CHECKING	AUTO-DETECTING WRONG BATTERY CONT. ex. 12V / 24V	AUTO-DETECTING WRONG BATTERY CONT. ex. 12V / 24V
※ OUTPUT REGULATION	± 5% INTELLIGENT AVR	± 5% INTELLIGENT AVR
※ OUTPUT FREQUENCY	50Hz , 55Hz , 60Hz CRYSTAL CONTROLLED.	50Hz , 55Hz , 60Hz CRYSTAL CONTROLLED.
※ COOLING	AUTO-OPERATION FAN	AUTO-OPERATION FAN
PROTECTIONS:		
※ OUTPUT SHORT	OUTPUT SHORT CIRCUIT PROTECTION	OUTPUT SHORT CIRCUIT PROTECTION
※ LOW BATTERY	< 10.5V ± 0.5V PRE-ALARM < 9.5V ± 0.5V SHUT DOWN & ALARM	< 21.5V ± 0.5V PRE-ALARM < 20V ± 0.5V SHUT DOWN & ALARM
※ OVER HEATING	> 60°C PRE-ALARM > 65°C SHUT DOWN & ALARM	> 60°C PRE-ALARM > 65°C SHUT DOWN & ALARM
※ OVER LOAD	> 650W PRE-ALARM > 700W SHUT DOWN & ALARM	> 650W PRE-ALARM > 700W SHUT DOWN & ALARM
BATTERY POLARITY REVERSE	BY FUSE	BY FUSE
FUSE	DC 12V : 25A * 3PCS	DC 24V : 20A * 3PCS
AC OUTLET	UK TYPE : 1 AC OUTLET	UK TYPE : 1 AC OUTLET
DIMENSION (L*W*H)	200*173*60mm	200*173*60mm
NET WEIGHT	2Kg	2Kg

※ MARK ARE OUR UNIQUE FUNCTIONS